



2022-01-01

Technical data

PRODUCT: SOFTSTEP

Type		Rigid vinyl flooring, SPC, Resilient floor coverings, Heterogeneous
Usage classification	10874:2009	Domestic: 23 Commercial: 33 Industrial: 41
Dimensions		
Thickness wear layer		0,55 mm
Thickness		6 mm (incl 1 mm cork underlay)
Length and width		180 x 1220 mm, 305 x 610 mm
Dimensional stability	23999:2008	< 0,05 %
Residual indentation	24343-1:2007	< 0,05 mm
Locking strength	10582:2017	Long side 7,6 kN/m, Short side 6,3 kN/m
Resistance to staining	26987:2008	Not affected
Slip resistance	51130:2014-02	R10
Resistance to bacteria	846-1997 M C	No bacteria growth on surface
Reaction to fire	13501-1	B _{fl} -s1
Phthalate	14372:2004	Not detected
Floor heating		Approved. Maximum temperature on surface > 27 °C
Sound reduction	712/2	19 dB
Click system		Unipush
Subfloor evenness		3 mm over 2 m 2 mm over 1 m 1,2 mm over 0,25 m
Warranty		20 years limited warranty

Organisationsnummer	556695-2148	
Postadress: Miljöagenturer AB Box 126 S-521 02 FALKÖPING	Kontor: Bergsängsvägen 62A S-521 30 FALKÖPING	Telefon: 0515-77 64 90
SWIFT: NDEASESS	IBAN: SE27 3000 0000 0170 5170 1789	