



2023-01-01

## Technical data

**PRODUCT:** SOFTSTEP

<b>Type</b>		Rigid vinyl flooring, SPC, Resilient floor coverings, Heterogeneous
<b>Usage classification</b>	10874:2009	Domestic: 23 Commercial: 33 Industrial: 41
<b>Dimensions</b>		
Thickness wear layer		0,55 mm
Thickness		6 mm (incl 1 mm cork underlay)
Length and width		180 x 1220 mm, 305 x 610 mm
<b>Dimensional stability</b>	23999:2008	< 0,05 %
<b>Residual indentation</b>	24343-1:2007	< 0,05 mm
<b>Locking strength</b>	10582:2017	Long side 7,6 kN/m, Short side 6,3 kN/m
<b>Resistance to staining</b>	26987:2008	Not affected
<b>Slip resistance</b>	51130:2014-02	R10
<b>Resistance to bacteria</b>	846-1997 M C	No bacteria growth on surface
<b>Reaction to fire</b>	13501-1	B <sub>fl</sub> -s1
<b>Phthalate</b>	14372:2004	Not detected
<b>Floor heating</b>		Approved. Maximum temperature on surface 27 °C
<b>Sound reduction</b>	712/2	19 dB
<b>Click system</b>		Unipush
<b>Subfloor evenness</b>		3 mm over 2 m 2 mm over 1 m 1,2 mm over 0,25 m
<b>Warranty</b>		20 years limited warranty

<b>Organisationsnummer</b>	556695-2148	
<b>Postadress:</b> Miljöagenturer AB Bergsängsvägen 62A 521 30 FALKÖPING	<b>E-post:</b> info@miljoagenturer.se	<b>Telefon:</b> 0515-77 64 90